


## 2.4 GHz 30 dBi Directional Reflector Grid Wireless LAN Antenna Model: ANDES-DG-2.4-30



### Applications and Features

#### Applications


- \* 2.4 GHz ISM Band
- \* IEEE 802.11b, 802.11g Wireless LAN
- \* IEEE 802.11n (Pre-N, Draft-N, MIMO) Applications
- \* WiFi Systems
- \* Long-range Directional Applications
- \* Point to Point Systems
- \* Point to Multi-point Systems



- \* Wireless Bridges
- \* Backhaul Applications
- \* Wireless Video Systems

#### Features

- \* Superior performance
- \* Welded galvanized steel construction
- \* UV stable light gray powder coat finish
- \* All weather operation
- \* 5.3° beam-width
- \* 18 inch coax lead
- \* Two piece reflector grid significantly reduces shipping costs
- \* RoHS Compliant



### Description

#### Superior Performance

The WWP-DG-2.4-30 High Performance Parabolic Grid WiFi Antenna provides 30 dBi gain with a 5.3° beam-width for highly directional long range applications. Additional applications include point to point systems, point to multi-point and wireless bridges in the 2.4GHz ISM band as well as IEEE 802.11b, 802.11g and 802.11n wireless LAN systems. External interference of this antenna is minimized due to the excellent front to back ratio. This antenna comes with a 18" coax lead terminated with an N-Female connector.

#### Rugged and Weatherproof

This antenna's construction features a welded steel reflector grid for superior strength. The grid surface is UV powder coated for durability and aesthetics, and the open-frame design minimizes wind loading.


#### Two Piece Design

The desing exclusive, this antenna's 2-piece reflector grid is simple to assemble. The 2-piece design significantly reduces shipping costs compared to similar antennas with one piece reflector grids.

The The WWP-DG-2.4-30 antenna is supplied with a heavy duty 30 degree tilt and swivel mast mount kit. This allows installation at various degrees of incline for easy alignment. It can be adjusted up or down from 0° to 30°. It can be mounted to a 1.5" (38mm) to 3" (76mm) dia. mast.

# 2.4 GHz 30 dBi Directional Reflector Grid Wireless LAN Antenna

Model: ANDES-DG-2.4-30



## Specifications

### Electrical Specifications

<b>Frequency:</b>	2400-2500 MHz
<b>Gain:</b>	30 dBi
<b>Horizontal Beam Width:</b>	5.3°
<b>Vertical Beam Width:</b>	5.3°
<b>Front to Back Ratio:</b>	> 30 dB
<b>Impedance:</b>	50 Ohm
<b>Max Power:</b>	100 Watts
<b>VSWR:</b>	< 1.5:1 avg.
<b>Frequency:</b>	2400-2500 MHZ


### Mechanical Specifications

<b>Weight:</b>	35 lbs. (16 kg)
<b>Dimensions:</b>	59" Dia. (1.5 m)
<b>Mounting:</b>	1.5" (38mm) to 3" (76mm) dia. mast
<b>Grid Material:</b>	Galvanized Steel
<b>Polarization:</b>	Vertical
<b>Operating Temperature:</b>	-40° C to to 85° C (-40° F to 185° F)
<b>RoHS Compliant:</b>	Yes
<b>Wind Survival:</b>	134 MPH

### Wind Loading Data

<b>Wind Speed (MPH):</b>	100 125
<b>Loading:</b>	61.8 lb 97 lb.

2.4 GHz 30 dBi Directional Reflector  
Grid Wireless LAN Antenna  
Model: ANDES-DG-2.4-30



RF Antenna Gain Patterns

